



Color Code	
BlackK
BlueB
RedR
GreenG
OrangeO
YellowY

D.O.T. TYPE "A" NON-REINFORCED AIR BRAKE TUBING

Features:

- Ideal for use on vehicles for instrumentation and pneumatic accessories connected to the air brake system.
- Meets SAE specifications J844 Type "A".
- Heat and light stabilized.
- 150 PSI maximum working pressure; - 40° F to 200° F temperature range.

Tube O.D.	Wall Thickness	Bend Radius	Burst Pressure at 70° F	Weight per 100'	Tubing Length	Model
1/8"	.023 ± .003	3/8"	1000 PSI	.34 lb.	1000'	ADOT18-1000 color
5/32"	.032 ± .003	1/2"	1200 PSI	.57 lb.	1000'	ADOT532-1000 color
3/16"	.035 ± .003	3/4"	1200 PSI	.77 lb.	1000'	ADOT316-1000 color
1/4"	.040 ± .003	1"	1200 PSI	1.21 lbs.	1000'	ADOT14-1000 color
5/16"	.040 ± .004	1 1/4"	1000 PSI	1.57 lbs.	500'	ADOT516-500 color

BALL SWIVEL LEAD-IN HOSE

Features:

- When used between the tool and coupler, a lead-in hose will extend the life of the coupler by acting as a shock absorber and protecting against tool vibration.
- Ball swivel provides an easier and wider range of motion.
- Maximum working pressures: Flexeel® – 200 PSI; Red Rubber – 250 PSI.
- Fittings are male ball swivel and female rigid.



NPT	Hose I.D.	Hose Length	Flexeel Model	Red Rubber Model
1/4"	1/4"	12"	A750DD12BS	A720DD12BS
1/4"	1/4"	18"	A750DD18BS	A720DD18BS
1/4"	1/4"	24"	A750DD24BS	A720DD24BS
1/4"	1/4"	30"	A750DD30BS	A720DD30BS
1/4"	1/4"	36"	A750DD36BS	A720DD36BS
1/4"	1/4"	60"	A750DD60BS	A720DD60BS
1/4"	3/8"	12"	A750FD12BS	A720FD12BS
1/4"	3/8"	18"	A750FD18BS	A720FD18BS
1/4"	3/8"	24"	A750FD24BS	A720FD24BS
1/4"	3/8"	30"	A750FD30BS	A720FD30BS
1/4"	3/8"	36"	A750FD36BS	A720FD36BS
1/4"	3/8"	60"	A750FD60BS	A720FD60BS
1/4"	3/8"	72"	A750FD72BS	A720FD72BS

WORM DRIVE REUSABLE HOSE CLAMPS

Features:

- Facilitate quick, permanent in-the-field installation and repairs.
- Makes custom hose assemblies possible using only a screwdriver.
- Band and housing are made of heavy duty stainless steel and the screw is available in cadmium-plated steel or stainless steel.



NOTE: Clamps are sold in package quantities only.

Size Range (Diameter)	Band Width	Package Quantity	Cadmium-Plated Model	Stainless Model
7/32" Min. - 5/8" Max.	5/16"	10	A4104	A5104
5/16" Min. - 7/8" Max.	5/16"	10	A4106	A5106
11/16" Min. - 1 1/2" Max.	5/16"	10	A4116	A5116

BRASS HOSE FERRULES

NOTE: Brass hose ferrules are sold in package quantities only.

I.D.	Length	Package Quantity	Model
0.562"	3/4"	25	A788
0.525"	1"	25	A790
0.625"	1"	25	A792
0.656"	1"	25	A795
0.687"	1"	25	A796
0.718"	1"	25	A797
0.750"	1"	25	A798

